

RAVENOL Super HD 30

SAE: 30W

Mineral



1 l

Vendor:
1113300-001
 Vendor:
 1113300-001-01-999



4 l

Vendor:
1113300-004
 Vendor:
 1113300-004-01-999



5 l

Vendor:
1113300-005
 Vendor:
 1113300-005-01-999



10 l

Vendor:
1113300-010



20 l

Vendor:
1113300-020
 Vendor:
 1113300-020-01-999



20 l, ecobox

Vendor:
1113300-B20



60 l

Vendor:
1113300-060
 Vendor:
 1113300-060-01-999



208 l

Vendor:
1113300-208
 Vendor:
 1113300-208-01-999



1 000 l

Vendor:

1113300-700

RAVENOL Super HD 30 is mineral mono grade engine oil for passenger car gasoline and diesel engines with and without turbocharging, and is also suitable for commercial vehicle engines and vans under light loads which require this grade of oil. Designed to minimize friction and wear, the formulation ensures year round high lubricity throughout all operating conditions. Extended oil drain capability where recommended by the vehicle manufacturer.

Application Note

RAVENOL Super HD 30 is suitable for both gasoline and diesel engines in cars, van and commercial vehicles which require this grade of engine oil.

Characteristics

- Corrosion protection
- Good shear stability
- High oxidation stability
- Excellent viscosity-temperature behavior
- Enhanced levels of detergent and dispersant for cleaner engines
- Very good cold starting properties
- Prevents formation of deposits and black sludge

Characteristics

Title	Value	Audit
API	CD, SF	
Համապատասխանում է արտադրողի պահանջներին	CCMC G4, MB 227.0, MIL-L-2104 D, MIL-L-46152 B	
Density at 20 °C	876 kg/m ³	EN ISO 12185
Գույն	Brown	տեսողական
Մածուցիկություն 100 °C-ում	12.1 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	103.3 mm ² /s	DIN 51562-1
Viscosity Index VI	106	DIN ISO 2909
Pourpoint	-27 °C	DIN ISO 3016
Flashpoint	248 °C	DIN EN ISO 2592
TBN	7.2 mgKOH/g	ASTM D2896

Out of production

Product	Vendor	Barcode
1 l	1113300-001-01-000	
	1113300-001-06-999	
10 l	1113300-010-01-999	