

RAVENOL MARINEOIL PETROL 15W-40

SAE: 15W-40**Mineral****1 l**Vendor:
1163200-001**4 l**Vendor:
1163200-004**10 l**Vendor:
1163200-010**20 l**Vendor:
1163200-020**20 l, ecobox**Vendor:
1163200-B20**60 l**Vendor:
1163200-060**208 l**Vendor:
1163200-208

RAVENOL MARINEOIL PETROL SAE 15W-40 is a high additive treated HD engine oil for marine gasoline engines.

RAVENOL MARINEOIL PETROL SAE 15W-40 is especially produced for extended oil change intervals (under consideration of the manufacturer instruction).

Application Note

RAVENOL MARINEOIL PETROL SAE 15W-40 is tried and tested for aggregates specifying:

Specification: API SL

Recommendations: VOLVO Penta AB, Mercruiser, Yanmar, Kohler

Characteristics

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions

Characteristics

Title	Value	Audit
API	SL	
Համապատասխանում է արտադրողի պահանջներին	Volvo Penta AB	
Suitable for	Kohler, Mercruiser, Yanmar	
Density at 20 °C	879.5 kg/m ³	EN ISO 12185
Գույն	Blue	տեսողական
Մածուցիկություն 100 °C-ում	15 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	115.7 mm ² /s	DIN 51562-1
Viscosity Index VI	134	DIN ISO 2909
Pourpoint	-36 °C	DIN ISO 3016
Flashpoint	238 °C	DIN EN ISO 2592
TBN	10.5 mgKOH/g	ASTM D2896

Out of production

Product	Vendor	Barcode
1 l	1163200-001-01-999	
4 l	1163200-004-01-999	
10 l	1163200-010-01-999	
20 l	1163200-020-01-999	
60 l	1163200-060-01-999	
208 l	1163200-208-01-999	