

RAVENOL MARINEOIL PETROL 20W-50

SAE: 20W-50**Mineral****1 l**Vendor:
1163210-001**4 l**Vendor:
1163210-004
Vendor:
1163210-004-01-999
Barcode:
4014835730397**10 l**Vendor:
1163210-010**20 l**Vendor:
1163210-020**20 l, ecobox**Vendor:
1163210-B20**60 l**Vendor:
1163210-060**208 l**Vendor:
1163210-208**1 000 l**Vendor:
1163210-700

RAVENOL MARINEOIL PETROL 20W-50 is a multi-range engine oil for marine gasoline engines.

RAVENOL MARINEOIL PETROL 20W-50 corresponds to the demands of the SAE class 20W-50. This viscosity classification guarantees a good lubricating film also under complicate operating conditions.

Characteristics

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions
- a good water separation behaviour

Characteristics

Title	Value	Audit
API	SL	
Համապատասխանում է արտադրողի պահանջներին	Volvo Penta AB	
Suitable for	Kohler, Mercruiser, Yanmar	
Density at 20 °C	878.2 kg/m ³	EN ISO 12185
Գույն	Blue	տեսողական
Մածուցիկություն 100 °C-ում	18.5 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	161 mm ² /s	DIN 51562-1
Viscosity Index VI	129	DIN ISO 2909
Pourpoint	-36 °C	DIN ISO 3016
Flashpoint	247 °C	DIN EN ISO 2592
TBN	10.7 mgKOH/g	ASTM D2896
Sulphated Ash	1.42 %wt.	DIN 51575
Engine cycle	4T	

Out of production

Product	Vendor	Barcode
1 l	1163210-001-01-999	
	1163210-001-06-999	
10 l	1163210-010-01-999	
20 l	1163210-020-01-999	
60 l	1163210-060-01-999	
208 l	1163210-208-01-999	