

RAVENOL MARINEOIL SHPD 25W-40 mineral

SAE: 25W-40**Mineral****1 l**Vendor:
1163215-001**4 l**Vendor:
1163215-004**10 l**Vendor:
1163215-010**20 l**Vendor:
1163215-020
Vendor:
1163215-020-01-999
Barcode:
4014835730427**20 l, ecobox**Vendor:
1163215-B20**60 l**Vendor:
1163215-060**208 l**Vendor:
1163215-208**1 000 l**Vendor:
1163215-700

RAVENOL MARINEOIL SHPD SAE 25W-40 mineral is a modern high additive treated marine engine oil with synthetic additives. It is suitable for inboard marine diesel engines. The high additive content guarantees an excellent effect on the detergent, dispersant and anti corrosion characteristics. It is a top quality product with high safety reserves.

Application Note

RAVENOL MARINEOIL SHPD SAE 25W-40 mineral is used in boat engines in case the specification SAE25W-40 is requested.

Characteristics

- suitability for catalysts
- excellent detergent and dispersant characteristics
- very good cold start characteristics
- a high oxidation stability
- an excellent viscosity temperature behaviour
- an excellent corrosion protection
- high safety reserves
- reduction of emissions

Characteristics

Title	Value	Audit
API	CF	
Համապատասխանում է արտադրողի պահանջներին	DDC Detroit Diesel, VETUS DEUTZ, Volvo PENTA	
Suitable for	Caterpillar, IVECO, MAN, MTU, Mercruiser, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, Yanmar	
Density at 20 °C	876 kg/m ³	EN ISO 12185
Գույն	Blue	տեսողական
Մածուցիկություն 100 °C-ում	19 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	161.4 mm ² /s	DIN 51562-1
Viscosity Index VI	133	DIN ISO 2909
CCS Viscosity at -15 °C	6100 mPa*s	ASTM D5293
Pourpoint	-30 °C	DIN ISO 3016
Flashpoint	245 °C	DIN EN ISO 2592
TBN	11.1 mgKOH/g	ASTM D2896
Engine cycle	4T	

Out of production

Product	Vendor	Barcode
1 l	1163215-001-01-999	
	1163215-001-06-999	
4 l	1163215-004-01-999	
10 l	1163215-010-01-999	
60 l	1163215-060-01-999	
208 l	1163215-208-01-999	