

RAVENOL Truck MTF-50

Full synthetic



1 l

Vendor:
1221106-001
Vendor:
1221106-001-01-999



4 l

Vendor:
1221106-004
Vendor:
1221106-004-01-999



10 l

Vendor:
1221106-010



20 l

Vendor:
1221106-020
Vendor:
1221106-020-01-999



60 l

Vendor:
1221106-060
Vendor:
1221106-060-01-999



208 l

Vendor:
1221106-208
Vendor:
1221106-208-01-999

RAVENOL Truck MTF-50 is a full synthetic heavy duty manual transmission oil requiring a non-EP lubricant.

RAVENOL Truck MTF-50 is based on synthetic base oils and special additives matched to them. Thus, the extended requirements of Eaton axle and transmission divisions are fulfilled.

RAVENOL Truck MTF-50 is ideally suited for severe operating conditions and extended oil change intervals.

Application Note

RAVENOL Truck MTF-50 is recommended for extended drain and severe service in heavy duty (class 6, 7, and 8) manual transmissions requiring a non-EP lubricant.

Characteristics

- Excellent thermal stability.
- Strong protection against rust, corrosion and foaming.
- A very low pour point.
- Excellent EP properties.
- A good switching behavior at low temperatures.
- An extended service life.
- Fuel savings.

Characteristics

Title	Value	Audit
API	MT-1	
Համապատասխանում է արտադրողի պահանջներին	Arvin Meritor 0-81, Eaton PS-164 Rev. 7, International Harvester TMS-6816, Mack TO-A Plus, ZF FreedomLine, ZF TE-ML 02L	
Density at 20 °C	857 kg/m ³	EN ISO 12185
Գույն	Brown	տեսողական
Մածուցիկություն 100 °C-ում	17.5 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	132 mm ² /s	DIN 51562-1
Viscosity Index VI	146	DIN ISO 2909
Brookfield Viscosity at -26 °C	16.900 mPa*s	ASTM D2983
Pourpoint	-45 °C	DIN ISO 3016
Flashpoint	221 °C	DIN EN ISO 2592
Copper Strip Test at 121 °C	1a	ASTM D130

Out of production

Product	Vendor	Barcode
10 l	1221106-010-01-999	