

RAVENOL Getriebeoel SLS 75W-140 GL 5 LS

SAE: 75W-140

Synthetic



1 L

Vendor:
1221110-001
Vendor:
1221110-001-01-999
Barcode:
4014835734012



4 L

Vendor:
1221110-004
Vendor:
1221110-004-01-999
Barcode:
4014835734098



10 L

Vendor:
1221110-010
Vendor:
1221110-010-01-999
Barcode:
4014835734043



20 L

Vendor:
1221110-020



20 L, ecobox

Vendor:
1221110-B20



60 L

Vendor:
1221110-060



208 L, տպագիր տակառ

Vendor:
1221110-D60



208 L

Vendor:
1221110-208



208 լ տպագիր տակառ

Vendor:
1221110-D28
Vendor:
1221110-D28-01-888
Barcode:
4014835734005



1 000 լ

Vendor:
1221110-700

RAVENOL Getriebeoel SLS SAE 75W-140 GL 5 LS is a power class API GL-5 synthetic multi-grade hypoid transmission oil for manual transmissions and rear-axles in many popular vehicles. It is suitable for highly stressed hypoid axle drives as well as spur- and bevel gears, change gears in vehicles and work machines as well as steering gears also requiring "limited slip" properties.

RAVENOL Getriebeoel SLS SAE 75W-140 GL 5 LS is PAO based with a specially coordinated additive treatment. This exceeds the needs of today's application requirements.

RAVENOL Getriebeoel SLS SAE 75W-140 GL 5 LS is outstanding for use as a rationalization product also with respect to the new generation of 5- and 6-gear manual transmissions and axle drives with and without limited slip differential. Especially suited for applications requiring "limited slip" (LS) properties.

Application Note

RAVENOL Getriebeoel SLS SAE 75W-140 GL 5 LS is a high-performance transmission oil for maintaining manual transmissions and rear axles in many popular vehicles. Also suitable for highly stressed hypoid axle gears as well as spur- and bevel gears, change gears in vehicles and work machines, and steering gears. Particularly suited for applications requiring "limited slip" (LS) properties.

Characteristics

- A high pressure stable lubricating film even at high oil temperatures and under high stress.
- Outstanding shearing stability and excellent thermal stability.
- Excellent viscosity-temperature properties.
- High oxidation stability.
- Excellent wear protection, outstanding EP properties.
- Low foaming properties even at high speeds.
- Good compatibility with non-ferrous metals and sealing materials.
- Good shifting behaviour even in low temperatures, low pour point.
- Extended life.
- Well adhering lubricating film and outstanding LS additive treatment for reduced transmission noise even when oil is hot.

Characteristics

Title	Value	Audit
API	GL-5 LS	
Համապատասխանում է արտադրողի պահանջներին	Ford WSL-M2C 192-A, MIL-L-2105 D	
Density at 20 °C	842.1 kg/m ³	EN ISO 12185
Գույն	Yellow	տեսողական
Մածուցիկություն 100 °C-ում	28.1 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	203.4 mm ² /s	DIN 51562-1
Viscosity Index VI	177	DIN ISO 2909
Brookfield Viscosity at -40 °C	127.600 mPa*s	ASTM D2983
Pourpoint	-51 °C	DIN ISO 3016
Flashpoint	220 °C	DIN EN ISO 2592
Copper Strip Test at 121 °C	1b	ASTM D130
Brookfield Viscosity at -50 °C	121.000 mPa*s	ASTM D2983

Analogs

Alpine

0100791, 0100794, 0100793, 100791, 100793, 100794, 100792, 0100792, 0100795, 100795

BMW

88889407870, 83229407803, 83222296631, 83222365988, 83222282583, 83229405462, 83229405463, 83229407870, 83229415961, 83229407871, 83229407804

BRP

779185, 293600138, 779156, 413802600, 413802800, 413803301, 219703336, 779179, 619590098, 413803300, 293600140, 619590182, 779160, 779215, 779161, 779170, 779211, 5639219, 6639147, 6639150, 4639025, 4639333, 4639361, 4639362, 4639364, 4639628

Chrysler

04874469AS, 82200945, 68197927AA, 68003055AA, 68218657CB, 68218658CA, 4874469, K68218657AA, K68218657GA, K68218658AA, 68218657CA, 68449547GA, 68218657GC, 68218657AC, VU01299, 68218657GB, 05103526EA, 68449547AA, 68218657AA, 68218657GA, 04874469, 68218658AA, 68218657AB, 68003055AB, 04874469AA

Ford

XY75W140QL1, F1TZ19580B, 7U7JM2C192AB, 190562, 3375657, XY75W140QL, 2606967, MU7JM2C192AA, 1836674, XY75W140KL, 1496946, 7U7JM2C192BA, 1836661, 7U7JM2C192BB

General Motors

89021524, 12346140, 9985991, 89021591, 1942386, 90393473, 89021809, 104053, 90485353, 89021801, 93165238,

1940775, 19280531

Jaguar

JLM20771

Land Rover

JLM21847

Mazda

000077W140QT, K004W0034S

Mercedes-Benz

A001989520310, A0019895203

Nissan

KLD4275401, KLD4175401, KE90790032U5, KE90790032U7, KE90790032, KE90799931, KE90790032EU, KE90799931R, 999MPDF100P, KLD4275401EU, KLD3114004

Opel

1940706

Polaris

2871280, 2871478

Scania

1892401, 1892403, 1892400, 1892402, 1892404, 2125324

Toyota

28975140, 0888500903, 0888500905, 0888500900

Volkswagen Group

G055145

Volvo

3809440, 3809438, 22574246, VP22574246, 3809439

Out of production

Product	Vendor	Barcode
1 l	1221110-001-01-000	4014835646711
	1221110-001-06-999	2200000019868
10 l	1221110-010-01-999	
20 l	1221110-020-01-999	
20 l, ecobox	1221110-B20-01-888	
60 l	1221110-060-01-999	
208 l	1221110-208-01-888	
	1221110-208-01-999	