

# RAVENOL Gear Super Synth GSS 75W-90

SAE: 75W-90

Full synthetic



**1 l**

Vendor:  
**1221123-001**  
 Vendor:  
 1221123-001-01-999



**4 l**

Vendor:  
**1221123-004**  
 Vendor:  
 1221123-004-01-999



**10 l**

Vendor:  
**1221123-010**  
 Vendor:  
 1221123-010-01-999  
 Barcode:  
 4014835872745



**20 l**

Vendor:  
**1221123-020**  
 Vendor:  
 1221123-020-01-999



**20 l, ecobox**

Vendor:  
**1221123-B20**  
 Vendor:  
 1221123-B20-01-888



**60 l**

Vendor:  
**1221123-060**  
 Vendor:  
 1221123-060-01-999



**60 l, տպագիր տակառ**

Vendor:  
**1221123-D60**  
 Vendor:  
 1221123-D60-01-888



**208 l**

Vendor:  
**1221123-208**  
 Vendor:  
 1221123-208-01-999  
 Barcode:  
 4014835872806



### 208 լ տպագիր տակառ

Vendor:  
**1221123-D28**  
Vendor:  
1221123-D28-01-888



### 1 000 լ

Vendor:  
**1221123-700**

**RAVENOL GEAR SUPER SYNTH GSS SAE 75W-90** is a full synthetic axle drive oil based on the latest full synthetic components for commercial vehicles.

**RAVENOL GEAR SUPER SYNTH GSS SAE 75W-90** is designed on the basis of high quality synthetic base oils with special additivation and inhibition, which ensure proper functioning of the gearbox.

## Application Note

**RAVENOL GEAR SUPER SYNTH GSS SAE 75W-90** is excellent for use in heavily loaded axle drives of commercial vehicles.

**RAVENOL GEAR SUPER SYNTH GSS SAE 75W-90** is suitable for non-synchronized manual transmissions, for which an oil according to API GL-5 or GL-4 is prescribed.

## Characteristics

- high additive reserves for prolonged oil change intervals according to the manufacturer instructions
- excellent cold flow properties
- good wear protection protects the gearbox
- Fuel savings even with short distances in low outside temperatures
- stable lubricating film even under high stress
- extreme low pour point
- Can be used at changing temperatures due to the high viscosity index

## Characteristics

Title	Value	Audit
API	GL-4, GL-5, MT-1	
Հաստատված է արտադրողի կողմից	MAN 341 Type Z2, MAN 342 Type S1, Scania STO 2:0 G, ZF TE-ML 02B, ZF TE-ML 05A, ZF TE-ML 12L, ZF TE-ML 12N, ZF TE-ML 16F, ZF TE-ML 17B, ZF TE-ML 19C, ZF TE-ML 21A	
Համապատասխանում է արտադրողի պահանջներին	Arvin Meritor 076-N, DDC 93K219.01, IVECO 18-1805, MAN 341 Type GA-2, Mack GO-J, Scania STO 2:0 A FS, Volvo 97312	
Համապատասխանում է արտադրողի բնութագրերին	MIL-PRF-2105 E, SAE J 2360	
Suitable for	DAF	
Density at 20 °C	873,0	EN ISO 12185
Գույն	Yellow	տեսողական
Մածուցիկություն 100 °C-ում	14.82 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	108.8 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	141	DIN ISO 2909
Brookfield Viscosity at -40 °C	97.000 mPa*s	ASTM D2983
Pourpoint	-54 °C	DIN ISO 3016
Flashpoint	186 °C	DIN EN ISO 2592
Seq. I at 24 °C	0/0 ml/ml	ASTM D892
Seq. II at 93,5 °C	0/0 ml/ml	ASTM D892
Seq. III at 24 °C after 93,5 °C	0/0 ml/ml	ASTM D892
Copper Strip Test at 121 °C	1a	ASTM D130