

RAVENOL Getriebeoel EPX 80W GL-5

SAE: 80W

Mineral



1 l

Vendor:
1223201-001



4 l

Vendor:
1223201-004



10 l

Vendor:
1223201-010



20 l

Vendor:
1223201-020



20 l, ecobox

Vendor:
1223201-B20



60 l

Vendor:
1223201-060



208 l

Vendor:
1223201-208



1 000 l

Vendor:
1223201-700

RAVENOL Getriebeoel EPX SAE 80 GL 5 was developed to eliminate seasonal transmission oil changes.

RAVENOL Getriebeoel EPX SAE 80 GL 5 guarantees due to the balanced additive combination characteristics like a high pressure absorption capacity, a superior viscosity temperature behaviour, a high oxidation stability, low pour points, a good corrosion protection and non-sludging.

Application Note

RAVENOL Getriebeoel EPX SAE 80 GL 5 is compatible with all name brand transmission oils. No “flushing” required when switching to **RAVENOL Getriebeoel EPX SAE 80 GL 5**

Use **RAVENOL Getriebeoel EPX SAE 80 GL 5** in hypoid gears for hypoid gearbox, manual transmissions, axle drives, distributor and intermediate transmissions in vehicles and working machines.

Characteristics

- Optimal cold flow property
- Outstanding wear protection even with short trips in winter
- High pressure stable lubrication film, thus outstanding wear protection under any stress
- Reduced transmission noise and the best transmission efficiency under full load, i.e. even with very hot oil
- Outstanding shearing stability
- Excellent oxidation stability, no foaming
- No oil thickening or deposits
- Extraordinary ageing stability
- Excellent viscosity-temperature properties
- Effective wear protection
- Extraordinary corrosion protection, no rust, won't harm non-ferrous metals
- Neutral to sealants, transmissions stay tight, no oil loss

Characteristics

Title	Value	Audit
API	GL-5	
Համապատասխանում է արտադրողի պահանջներին	DTFR 12B100 (MB 235.0), Ford SQ-M2C 9002-AA, MAN 342 Type M1, MB 235.0, MIL-L-2105 D, VOLVO 97313, ZF TE-ML 05A, ZF TE-ML 07A, ZF TE-ML 16B, ZF TE-ML 16C, ZF TE-ML 16D, ZF TE-ML 17B	
Density at 20 °C	882 kg/m ³	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	14.3 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	130.3 mm ² /s	DIN 51562-1
Viscosity Index VI	108	DIN ISO 2909
Pourpoint	-33 °C	DIN ISO 3016
Flashpoint	222 °C	DIN EN ISO 2592
Copper Strip Test at 121 °C	1b	ASTM D130
Brookfield Viscosity at -26 °C	60.100 mPa*s	ASTM D2983

Out of production

Product	Vendor	Barcode
1 l	1223201-001-01-999 1223201-001-06-999	
4 l	1223201-004-01-999	
10 l	1223201-010-01-999	
20 l	1223201-020-01-999	
20 l, ecobox	1223201-B20-01-888	
60 l	1223201-060-01-999	
208 l	1223201-208-01-999	