

RAVENOL MOTOGEAR 80W-90 GL-4

SAE: 80W-90

Mineral



1 l

Vendor:
1250055-001
 Vendor:
 1250055-001-01-999
 Barcode:
 4014835735217



4 l

Vendor:
1250055-004



20 l ecobox

Vendor:
1250055-B20



208 l

Vendor:
1250055-208

RAVENOL MOTOGEAR SAE 80W-90 GL-4 is a transmission fluid on a mineral oil basis with special effective additives for manual transmissions. A high load-carrying capacity guarantees optimum gearbox lubrication even at high temperatures.

RAVENOL MOTOGEAR SAE 80W-90 GL-4 ensures a strong oil film for lubrication even under the most extreme dynamic conditions.

RAVENOL MOTOGEAR SAE 80W-90 GL-4 reduces friction, prevents wear and corrosion.

Application Note

RAVENOL MOTOGEAR SAE 80W-90 GL-4 is suitable for use in manual transmissions for 2- and 4-stroke motorcycles if oil according to SAE 80W-90 API GL-4 is specified.

Characteristics

- Highly adhesive and pressure resistant lubricant films

- Excellent oxidation stability
- Above-average viscosity-temperature characteristics
- Wear-preventing effect
- A good air release property, no foaming
- Neutral behaviour towards metal and sealing compounds

Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
API	GL-4	
Density at 20 °C	879 kg/m ³	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	14 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	126.9 mm ² /s	DIN 51562-1
Viscosity Index VI	108	DIN ISO 2909
Brookfield Viscosity at -26 °C	45.600 mPa*s	ASTM D2983
Pourpoint	-33 °C	DIN ISO 3016
Flashpoint	244 °C	DIN EN ISO 2592
Copper Strip Test at 121 °C	1b	ASTM D130

Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
4 l	1250055-004-01-999	