

RAVENOL MOTOGEAR 80W-90 GL-5

SAE: 80W-90

Mineral



1 l

Vendor:
1250070-001
 Vendor:
 1250070-001-01-999
 Barcode:
 4014835735415



4 l

Vendor:
1250070-004



20 l

Vendor:
1250070-020



20 l, ecobox

Vendor:
1250070-B20

RAVENOL MOTOGEAR SAE 80W-90 GL-5 is a mineral based hypoid transmission fluid with special effective additives for manual transmissions. A high load-carrying capacity guarantees optimum gearbox lubrication even at high temperatures.

RAVENOL MOTOGEAR SAE 80W-90 GL-5 ensures a strong oil film for lubrication even under the most extreme dynamic conditions.

RAVENOL MOTOGEAR SAE 80W-90 GL-5 reduces friction, prevents wear and corrosion.

Application Note

RAVENOL MOTOGEAR SAE 80W-90 GL-5 is suitable for use in manual transmissions for 2- and 4-stroke motorcycles if oil according to SAE 80W-90 API GL-5 is specified.

Characteristics

- High pressure stable lubrication film, thus outstanding wear protection under any stress

- Reduced transmission noise and the best transmission efficiency under full load, i.e. even with very hot oil
- Excellent oxidation stability, no foaming
- No oil thickening or deposits
- Extraordinary ageing stability
- Excellent viscosity-temperature properties
- Effective wear protection
- Extraordinary corrosion protection, no rust, won't harm non-ferrous metals
- Neutral to sealants, transmissions stay tight, no oil loss

Characteristics

Title	Value	Audit
API	GL-5	
Density at 20 °C	882 kg/m ³	EN ISO 12185
Գույն	Brown	տեսողական
Մածուցիկություն 100 °C-ում	14.3 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	130.3 mm ² /s	DIN 51562-1
Viscosity Index VI	108	DIN ISO 2909
Pourpoint	-33 °C	DIN ISO 3016
Flashpoint	222 °C	DIN EN ISO 2592

Analogs

Suzuki

990F022930046

Yamalube

ACCSHAFTPL32

Out of production

Product	Vendor	Barcode
4 L	1250070-004-01-999	