

RAVENOL MOTOGEAR 10W-30 GL-4

SAE: 10W-30

Semi-synthetic



1 l

Vendor:
1250100-001
 Vendor:
 1250100-001-01-999
 Barcode:
 4014835735514



4 l

Vendor:
1250100-004



20 l

Vendor:
1250100-020

RAVENOL MOTOGEAR SAE 10W-30 GL-4 is a semi-synthetic special multi-grade transmission fluid which is specially formulated for air and water cooled 2 and 4-stroke engines with separate gearbox lubrication.

RAVENOL MOTOGEAR SAE 10W-30 GL-4 has an excellent lubricating film adhesion, excellent detergency and high resistance to aging.

RAVENOL MOTOGEAR SAE 10W-30 GL-4 enables a precise and soft changing of gears. Prevents clutch slippage.

RAVENOL MOTOGEAR SAE 10W-30 GL-4 forms a heavy-duty lubricant film, which is effective under all operating conditions.

Application Note

RAVENOL MOTOGEAR SAE 10W-30 GL-4 is designed for year-round use in all modern motorcycles of Japanese manufacturer's as YAMAHA.

Characteristics

- Quick lubrication of the engine at all operating temperatures.
- Heavy-duty lubricant film under all operating conditions.
- Precise, soft changing of gears, no clutch slippage.
- Reliability due to excellent lubricant film adhesion, extraordinary purification capacity and outstanding ageing resistance.
- Neutral towards sealing compounds.

Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
API	GL-4	
Suitable for	Yamaha	
Density at 20 °C	858 kg/m ³	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	10.3 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	63.6 mm ² /s	DIN 51562-1
Viscosity Index VI	150	DIN ISO 2909
Pourpoint	-33 °C	DIN ISO 3016
Flashpoint	230 °C	DIN EN ISO 2592
TBN	7.4 mgKOH/g	ASTM D2896
Sulphated Ash	0.76 %wt.	DIN 51575
Անկայունություն NOACK	9.9 % M/M	ASTM D5800
Low Temp. Pumping viscosity (MRV) at -30 °C	12.300 mPa*s	ASTM D4684
CCS Viscosity at -25 °C	4830 mPa*s	ASTM D5293
HTHS մածուցիկություն 150 °C-ում	3.11 mPa*s	ASTM D5481

Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
4 L	1250100-004-01-999	