

RAVENOL MOTOGEAR 10W-40 GL-4

SAE: 10W-40

Semi-synthetic



1 l

Vendor:
1250101-001
 Vendor:
 1250101-001-01-999
 Barcode:
 4014835735613



4 l

Vendor:
1250101-004



20 l ecobox

Vendor:
1250101-B20

RAVENOL MOTOGEAR SAE 10W-40 GL-4 is a special multi-range transmission fluid on the basis of synthetic technology and special esters specifically formulated for easy gear changing even under extremely hard operating conditions.

RAVENOL MOTOGEAR SAE 10W-40 GL-4 is used in 2- and 4-stroke engines with separate gear lubrication and wet clutch systems.

RAVENOL MOTOGEAR SAE 10W-40 GL-4 enables a precise and soft changing of gears. Prevents clutch slippage. Forms a heavy-duty lubricant film, which is effective under all operating conditions.

RAVENOL MOTOGEAR SAE 10W-40 GL-4 is used in motorcycles from Japanese and European manufacturers.

Application Note

RAVENOL MOTOGEAR SAE 10W-40 GL-4 is used in 2- and 4-stroke engines with separate gear lubrication and wet clutch systems.

RAVENOL MOTOGEAR SAE 10W-40 GL-4 enables a precise and soft changing of gears. Prevents clutch slippage. Forms a heavy-duty lubricant film, which is effective under all operating conditions.

Characteristics

- Quick lubrication of the engine at all operating temperatures.
- Heavy-duty lubricant film under all operating conditions.
- Precise, soft changing of gears, no clutch slippage.
- Reliability due to excellent lubricant film adhesion, extraordinary purification capacity and outstanding ageing resistance.
- Neutral towards sealing compounds.

Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
API	GL-4	
Density at 20 °C	862 kg/m ³	EN ISO 12185
Քույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	14 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	91.3 mm ² /s	DIN 51562-1
Viscosity Index VI	157	DIN ISO 2909
Pourpoint	-36 °C	DIN ISO 3016
Flashpoint	238 °C	DIN EN ISO 2592
TBN	9.5 mgKOH/g	ASTM D2896
Sulphated Ash	1.5 %wt.	DIN 51575

Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
4 l	1250101-004-01-999	