

RAVENOL STOU 10W-40

SAE: 10W-40**5 l**Vendor:
1310111-005**10 l**Vendor:
1310111-010**20 l**Vendor:
1310111-020
Vendor:
1310111-020-01-999
Barcode:
4014835739826**20 l, ecobox**Vendor:
1310111-B20**60 l**Vendor:
1310111-060**208 l**Vendor:
1310111-208**1 000 l**Vendor:
1310111-700

RAVENOL STOU SAE 10W-40 is an up-to-date multifunctional lubricating oil for agricultural machinery, excavators and construction machinery and is formulated with top-grade solvent refined base oils and additives.

RAVENOL STOU SAE 10W-40 meets the recommendations of all well known tractor manufacturers and is equal to use in engines, transmissions and hydraulic systems of modern tractors. Ensures trouble-free operation of all units in all seasons.

Application Note

RAVENOL STOU SAE 10W-40 has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

RAVENOL STOU SAE 10W-40 is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as gear oil (including wet brakes) and as hydraulic oil.

Characteristics

- A powerful dispersion and detergency
- A high activity against wear, corrosion and foam
- A very strong resistance to oxidation
- A high and stable viscosity index
- An excellent extreme pressure properties

Characteristics

Title	Value	Audit
API	CG-4, GL-4, SF	
ACEA	E3	
Համապատասխանում է արտադրողի պահանջներին	Allison C-4, Case IH MS 1209, Caterpillar TO-2, DTFR 15B110 (MB 228.3), FENDT KDM 41.2011, Ford ESN-M2C 134-B, Ford ESN-M2C 134-C, Ford ESN-M2C 134-D, Ford ESN-M2C 159-B, Ford ESN-M2C 159-C, ISO VG 100 HVLP, ISO VG 68 HVLP, John Deere J20 C, John Deere J27, Kompressorenöl: Holman Compair Kompressor, MAN 271, MAT 3525, MB 227.1, MB 228.1, MB 228.3, MIL-L-2104 D, Massey Ferguson CMS M1139, Massey Ferguson CMS M1144, Massey Ferguson CMS M1145, New Holland NH 410B, ZF TE-ML 06A, ZF TE-ML 06B, ZF TE-ML 06C, ZF TE-ML 06D, ZF TE-ML 07B	
Suitable for	Atlas Copco Kompressor	
Density at 20 °C	864 kg/m ³	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	14.7 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	101.1 mm ² /s	DIN 51562-1
Viscosity Index VI	151	DIN ISO 2909
Pourpoint	-33 °C	DIN ISO 3016
Flashpoint	234 °C	DIN EN ISO 2592
TBN	12.4 mgKOH/g	ASTM D2896
Sulphated Ash	1.45 %wt.	DIN 51575

Out of production

Product	Vendor	Barcode
10 l	1310111-010-01-999	
60 l	1310111-060-01-999	
208 l	1310111-208-01-999	