

RAVENOL Catoel TO-4 10W

SAE: 10W

Mineral



20 L

Vendor:
1310610-020
 Vendor:
 1310610-020-01-999
 Barcode:
 4014835740228



20 L ecobox

Vendor:
1310610-B20



60 L

Vendor:
1310610-060



208 L

Vendor:
1310610-208
 Vendor:
 1310610-208-01-999
 Barcode:
 4014835740280



208 L տպագիր տակառ

Vendor:
1310610-D28



1 000 L

Vendor:
1310610-700

RAVENOL CATOEL TO-4 SAE 10W is a special oil for hydraulic- and transmission equipment.

RAVENOL CATOEL TO-4 SAE 10W fulfils the recommendations of Caterpillar TO-4 specification and is suitable for lubrication of power shift transmission, differentials, final drives and hydraulic equipment of earth-moving equipment, for which a Caterpillar TO-4 or Allison C-4 fluid is required.

Application Note

RAVENOL CATOEL TO-4 SAE 10W ensures maximum wear protection in various gears, such as side drives and differentials, optimized the friction coefficient in power shift transmissions, wet brakes and clutches and provides maximum service life of the units.

Characteristics

- Highest wear protection
- High oxidation stability
- Excellent viscosity-temperature behavior
- Optimization of friction coefficient behavior
- Guarantees maximum life of the units

Characteristics

Title	Value	Audit
API	CF, MT-1	
Հաստատված է արտադրողի կողմից	ZF TE-ML 03C	
Համապատասխանում է արտադրողի պահանջներին	Allison C-4, Caterpillar TO-4, Komatsu KES 07.868.1 (2002), ZF TE-ML 07F	
Suitable for	Eaton Fuller	
Density at 20 °C	860 kg/m ³	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	6.4 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	37.2 mm ² /s	DIN 51562-1
Viscosity Index VI	123	DIN ISO 2909
Pourpoint	-30 °C	DIN ISO 3016
Flashpoint	240 °C	DIN EN ISO 2592

Analogs

Caterpillar

143485, 7X7852

Volvo

15000659

Out of production

Product	Vendor	Barcode
208 l	1310610-208-01-000	4014835635180 2200000049254