

RAVENOL Hydraulikoel TS 68 (HLP)

SAE: 68**Mineral****1 l**Vendor:
1323106-001**5 l**Vendor:
1323106-005**20 l**Vendor:
1323106-020
Vendor:
1323106-020-01-999
Barcode:
4014835759527**20 l, ecobox**Vendor:
1323106-B20**60 l**Vendor:
1323106-060
Vendor:
1323106-060-01-999
Barcode:
4014835759565**208 l**Vendor:
1323106-208
Vendor:
1323106-208-01-999
Barcode:
4014835759589**1 000 l**Vendor:
1323106-700

RAVENOL Hydraulikoel TS 68 (HLP) is optimal alloyed mineral hydraulic oil with a high performance level and a wide application area of the whole industry.

RAVENOL Hydraulikoel TS 68 (HLP) with efficient additives offers an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

RAVENOL Hydraulikoel TS 68 (HLP) is characterised by good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection.

Application Note

RAVENOL Hydraulikoel TS 68 (HLP) is for universal use in all hydraulic systems.

RAVENOL Hydraulikoel TS 68 (HLP) is recommended in high performance hydraulic systems with high pressure pumps of all types, in sensitive control systems.

RAVENOL Hydraulikoel TS 68 (HLP) is used for hydraulic systems in agriculture, to supply small gearboxes and for use in circulating systems.

Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- neutrality of sealing materials

Characteristics

Title	Value	Audit
ASTM	D6158	
Համապատասխանում է արտադրողի պահանջներին	AFNOR NFE 48-603 HM, Bosch Rexroth RE 90220, Cetop RP 91H HM, Danieli Hydraulics, Eaton Vickers I-286-S, Eaton Vickers M-2950-S, FZG Test A 8,3/90, Fives Cincinnati P-55, Fives Cincinnati P-70, GB 111118.1 L-HM, GM LH-02-1-04, GM LS-2, Hoesch HWN 2333, ISO 11158 HM, MIL-PRF-17672 E, Müller , Parker Denison HF-0, Parker Denison HF-1, Parker Denison HF-2, SAE MS 1004 HM, SEB 181.222, SIS SS 155434, Sauer-Danfoss 520L0463, Swedish Standard 155434, U.S. Steel 126, U.S. Steel 127, U.S. Steel 136, VDMA 24318, Vickers M-2950-S, Vickers Pumpentest, ZF TE-ML 07H	
Համապատասխանում է արտադրողի բնութագրերին	DIN 51524-2, ISO 6743-4 HM	
Suitable for	Atos, Metso	
Density at 20 °C	866 kg/m ³	EN ISO 12185
Գույն	light yellow	տեսողական
Մածուցիկություն 100 °C-ում	9 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	68 mm ² /s	DIN 51562-1
Viscosity Index VI	106	DIN ISO 2909
Pourpoint	-27 °C	DIN ISO 3016
Flashpoint	256 °C	DIN EN ISO 2592

Analogs

Alpine

0100864, 0100865, 0100863

General Motors

88861695, 88861681

Out of production

Product	Vendor	Barcode
---------	--------	---------

1 l	1323106-001-01-999	
	1323106-001-06-999	
5 l	1323106-005-01-999	
20 l	1323106-020-01-999	
20 l	1323106-020-01-000	4014835641822
208 l	1323106-208-01-999	
208 l	1323106-208-01-000	4014835641884
		2200000048899