

RAVENOL Hydraulikoel TS AF 46

SAE: 46

Mineral

20 L

Vendor:

1323125-02060 L

Vendor:

1323125-060208 L

Vendor:

1323125-2081 000 L

Vendor:

1323125-700

RAVENOL Hydraulikoel TS AF 46 is a zinc and ash-free compounded oil based phosphorous and sulfur intended especially for use in the metal industry. Excellent results were achieved in the Timken test. Through the addition of selected ingredients, **RAVENOL Hydraulikoel TS AF 46** has excellent wear protection, good oxidation stability and has a long service life even under extreme conditions. Compatibility with sealants is neutral. Furthermore, the additives provide corrosion protection and prevent foaming.

RAVENOL Hydraulikoel TS AF 46 exceeds the requirements of DIN 51 524 part 2 for HLP hydraulic oils.

Application Note

RAVENOL Hydraulikoel TS AF 46 is for use as a hydraulic fluid in the metal industry, if zinc and ash-free hydraulic oil and the specification DIN 51 524, Part 2 is required.

Characteristics

- High performance level
- Good oxidation stability

- High resistance to ageing
- Outstanding wear protection
- High level of corrosion protection
- Neutral to sealants
- No foaming

Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի պահանջներին	FZG Test A 8,3/90, MAN N 698, SEB 181.222, SEB 181.226, Timken-Test DIN E 51434, Vickers Pumpentest	
Համապատասխանում է արտադրողի բնութագրերին	DIN 51524-2	
Density at 20 °C	862 kg/m³	EN ISO 12185
Գույն	Yellow	տեսողական
Մածուցիկություն 100 °C-ում	7.2 mm²/s	DIN 51562-1
Մածուցիկություն 40 °C-ում	46.4 mm²/s	DIN 51562-1
Viscosity Index VI	118	DIN ISO 2909
Pourpoint	-36 °C	DIN ISO 3016
Flashpoint	232 °C	DIN EN ISO 2592

Out of production

Product	Vendor	Barcode
20 L	1323125-020-01-999	
208 L	1323125-208-01-999	