

RAVENOL Hydraulikoel TSX 15 (HVLP)

SAE: 15**Mineral****1 l**Vendor:
1323202-001**5 l**Vendor:
1323202-005**20 l**Vendor:
1323202-020**20 l****20 l, ecobox**Vendor:
1323202-B20**60 l**Vendor:
1323202-060
Vendor:
1323202-060-01-999
Barcode:
4014835759961**208 l**Vendor:
1323202-208
Vendor:
1323202-208-01-999
Barcode:
4014835759985**1 000 l**Vendor:
1323202-700

RAVENOL Hydraulikoel TSX 15 (HVLP) is high quality multi-grade hydraulic oil type HVLP based on special selected solvent refined basic oils. It is characterised by a high stable viscosity index and a solid corrosion protection. Efficient additives offer an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

Application Note

RAVENOL Hydraulikoel TSX 15 (HVLP) is suitable for heavy loaded hydraulic machines of the industry, for earth moving machines and agricultural machines. Preferred use in case of great variations of the operation temperature. No use in case of silver and/or silver-coated components in the hydraulic machines.

Characteristics

- A high and stable viscosity index
- An excellent corrosion protection
- An excellent protection against wear
- A very good air and water separation behaviour to prevent foam formation
- Neutral behaviour towards sealing of plastics
- A very low pour point

Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի պահանջներին	AFNOR NFE 48-603 HV, AFNOR NFE 48-690/1, Bosch Rexroth RE 90220, Cetop RP 91H HV, GB 11118.1 L-HV, ISO 11158 HV, SAE MS 1004, Sauer-Danfoss 520L0463	
Համապատասխանում է արտադրողի բնութագրերին	DIN 51524-3, ISO 6743-4 HV	
Density at 20 °C	831 kg/m ³	EN ISO 12185
Գույն	Yellow	տեսողական
Մածուցիկություն 100 °C-ում	4.2 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	16.4 mm ² /s	DIN 51562-1
Viscosity Index VI	173	DIN ISO 2909
Pourpoint	-54 °C	DIN ISO 3016
Flashpoint	180 °C	DIN EN ISO 2592

Analogs

Scania
2252143

Out of production

Product	Vendor	Barcode
208 l	1323202-208-01-999	2200000049391
	1323202-208-01-000	4014835642386
208 l	1323202-208-01-909	4014835800182
	1323202-208-01-000	2200000049391 4014835642386