

RAVENOL Hydraulikoel HLP-D 32

SAE: 32W

Mineral

5 L

Vendor:

1323304-00520 L

Vendor:

1323304-02020 L ecobox

Vendor:

1323304-B20

Vendor:

1323304-B20-01-888

60 L

Vendor:

1323304-060208 L

Vendor:

1323304-208

Vendor:

1323304-208-01-999

Barcode:

4014835760684

1 000 L

Vendor:

1323304-700

RAVENOL Hydraulikoel HLP-D 32 is detergent hydraulic oil with good net and cleaning effect.

RAVENOL Hydraulikoel HLP-D 32 is designed with selected base oils with additives to prevent corrosion, wear and friction.

RAVENOL Hydraulikoel HLP-D 32 also contains detergent and dispersing agents, which always provide for a clean hydraulic system. These additives dissolve contaminants, hold them in suspension and enabling the cleaning of contaminated hydraulic systems. The functional elements of a hydraulic system thereby remain

free of deposits and bonds. This will emulsified penetrating water and ensure trouble-free operation of the hydraulic system.

RAVENOL Hydrauliköl HLP-D 32 is zinc and ash-free.

Application Note

RAVENOL Hydrauliköl HLP-D 32 is for use in agriculture hydraulic systems, construction machinery, cement factories, foundries, and electro-plate clutches. It can also be used as functional test oil, inlet oil for aggregates and machinery, textile machinery and machine tools.

Characteristics

- High aging resistance and high corrosion protection
- Good air release
- Excellent wear protection and proper conduct foam
- Very good viscosity-temperature behaviour
- neutral behaviour towards sealing materials
- Extremely good detergent and dispersant characteristics
- Excellent corrosion protection even at the ingress of wetness
- zinc and ash-free

Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի պահանջներին	Daimler DBL 6721, MAN N 698, Müller , Parker Denison HF-0	
Համապատասխանում է արտադրողի բնութագրերին	AFNOR NF E 48-603 HM, DIN 51524-2, ISO 11158 HM, ISO 6743-4 HM, JCMAS HK, SAE MS 1004 HM, SEB 181.222, U.S. Steel 127, U.S. Steel 136, VDMA 24318	
Density at 20 °C	865 kg/m³	EN ISO 12185
Գույն	tan	սեսողական
Մածուցիկություն 100 °C-ում	5.5 mm²/s	DIN 51562-1
Մածուցիկություն 40 °C-ում	31.8 mm²/s	DIN 51562-1
Viscosity Index VI	107	DIN ISO 2909
Pourpoint	-33 °C	DIN ISO 3016
Flashpoint	224 °C	DIN EN ISO 2592

Out of production

Product	Vendor	Barcode
5 L	1323304-005-01-999	
20 L	1323304-020-01-888 1323304-020-01-999	
60 L	1323304-060-01-999	