

RAVENOL ODL 32 Druckluftoel

SAE: 32W**Mineral****1 l**

Vendor:
1323404-001
Vendor:
1323404-001-01-999
Barcode:
4014835736610

**5 l**

Vendor:
1323404-005

**10 l**

Vendor:
1323404-010

**20 l**

Vendor:
1323404-020
Vendor:
1323404-020-01-999
Barcode:
4014835761124

**20 l, ecobox**

Vendor:
1323404-B20

**60 l**

Vendor:
1323404-060

**208 l**

Vendor:
1323404-208

RAVENOL ODL 32 Druckluftoel is a special-compressed-air-oil for pneumatic tools of all systems.

RAVENOL ODL 32 Druckluftoel bonds condensed water, has an excellent corrosion protection, wear protection and an extraordinary pressure absorption capacity, a good adhesive power and high aging resistance. Easily conveying- and spray ability, economy consumption. No deposits caused by cleaning effects. Full power of impact.

Application Note

RAVENOL ODL 32 Druckluftoel is especially suitable for pneumatic tools with sound-absorbing-case, for lubrication of rock drills, road breaker, chipping hammer and spade hammer, ram machines and other pneumatic aggregates. Application by pre-switch-lubricator according to working instructions or usable directly in the air pipe.

Please follow the manufacturer's instructions.

Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a good adherence
- a high aging resistance
- a reliable wear protection
- an excellent corrosion protection
- neutrality of sealing materials

Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
Համապատասխանում է արտադրողի պահանջներին	Black & Decker	
Suitable for	Atlas Copco Kompressor, Bosch, Cress, DeWalt, Festo, Hilti, Hitachi, Makita, Ryobi, Seno, Sumake	
Density at 20 °C	848 kg/m ³	EN ISO 12185
Գույն	light yellow	տեսողական
Մածուցիկություն 100 °C-ում	5.8 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	32.1 mm ² /s	DIN 51562-1
Viscosity Index VI	123	DIN ISO 2909
Pourpoint	-30 °C	DIN ISO 3016
Flashpoint	224 °C	DIN EN ISO 2592
FZG-Test A/8.3/90 Damage loading step	12 %wt.	DIN 51354/2

Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
1 l	1323404-001-01-100	4014835644311 2200000020789
5 l	1323404-005-01-999	
10 l	1323404-010-01-999	
60 l	1323404-060-01-999	
208 l	1323404-208-01-999	