

# RAVENOL ODL 46 Druckluftoel

**SAE: 46****Mineral****1 l**

Vendor:  
**1323405-001**  
Vendor:  
1323405-001-01-999  
Barcode:  
4014835736719

**5 l**

Vendor:  
**1323405-005**

**20 l**

Vendor:  
**1323405-020**  
Vendor:  
1323405-020-01-999  
Barcode:  
4014835761223

**20 l, ecobox**

Vendor:  
**1323405-B20**

**60 l**

Vendor:  
**1323405-060**

**208 l**

Vendor:  
**1323405-208**  
Vendor:  
1323405-208-01-999  
Barcode:  
4014835761285

**1 000 l**

Vendor:  
**1323405-700**

**RAVENOL ODL 46 Druckluftoel** is a special-compressed-air-oil for pneumatic tools of all systems.

**RAVENOL ODL 46 Druckluftoel** bonds condensed water, has an excellent corrosion protection, wear protection and an extraordinary pressure absorption capacity, a good adhesive power and high aging resistance. Easily conveying- and spray ability, economy consumption. No deposits caused by cleaning effects. Full power of impact.

## **Application Note**

**RAVENOL ODL 46 Druckluftoel** is especially suitable for pneumatic tools with sound-absorbing-case, for lubrication of rock drills, road breaker, chipping hammer and spade hammer, ram machines and other pneumatic aggregates. Application by pre-switch-lubricator according to working instructions or usable directly in the air pipe. Please follow the manufacturer's instructions.

## **Characteristics**

- a high performance level
- a very good viscosity temperature behaviour
- a good adherence
- a high aging resistance
- a reliable wear protection
- an excellent corrosion protection
- neutrality of sealing materials

## Characteristics

| Title                                   | Value  | Audit           |
|---|--|-----------------|
| Համապատասխանում է արտադրողի պահանջներին | Black & Decker   |                 |
| Suitable for                            | Atlas Copco Kompressor, Bosch, Cress, DeWalt, Festo, Hilti, Hitachi, Makita, Ryobi, Seno, Sumake |                 |
| Density at 20 °C                        | 857 kg/m <sup>3</sup>  | EN ISO 12185    |
| Գույն                                   | light yellow   | տեսողական       |
| Մածուցիկություն 100 °C-ում              | 7.2 mm <sup>2</sup> /s   | DIN 51562-1     |
| Մածուցիկություն 40 °C-ում               | 47 mm <sup>2</sup> /s  | DIN 51562-1     |
| Viscosity Index VI                      | 113  | DIN ISO 2909    |
| Pourpoint                               | -27 °C   | DIN ISO 3016    |
| Flashpoint                              | 238 °C   | DIN EN ISO 2592 |
| Demulsification                         | 40ml/40ml/10min.   | DIN 51757       |
| Ծերացման կայունություն, TOST            | 2000 st  | DIN 51587       |
| FZG-Test A/8.3/90 Damage loading step   | 12 %wt.  | DIN 51354/2     |

## Out of production

| Product | Vendor             | Barcode       |
|---------|--------------------|---------------|
| 1 l     | 1323405-001-01-100 | 4014835644014 |
|         | 1323405-001-06-999 | 2200000023735 |
| 5 l     | 1323405-005-01-999 |               |
| 20 l    | 1323405-020-01-100 | 4014835644021 |
| 60 l    | 1323405-060-01-999 |               |