

# RAVENOL Kompressoren-Oel VDL 150

SAE: 150

Mineral



**1 l**

Vendor:  
**1330101-001**  
 Vendor:  
 1330101-001-01-999  
 Barcode:  
 4014835757011



**5 l**

Vendor:  
**1330101-005**  
 Vendor:  
 1330101-005-01-999  
 Barcode:  
 4014835757059



**10 l**

Vendor:  
**1330101-010**  
 Vendor:  
 1330101-010-01-999  
 Barcode:  
 4014835757042



**20 l**

Vendor:  
**1330101-020**  
 Vendor:  
 1330101-020-01-999  
 Barcode:  
 4014835757028



**20 l, ecobox**

Vendor:  
**1330101-B20**



**60 l**

Vendor:  
**1330101-060**



**208 l**

Vendor:  
**1330101-208**  
 Vendor:  
 1330101-208-01-999  
 Barcode:  
 4014835757080



**1 000 l**

Vendor:  
**1330101-700**

**RAVENOL Kompressorenoel VDL 150** meets the high requirements of DIN 51506. Specifically designed with premium quality and age-resistant base oils.

**RAVENOL Kompressorenoel VDL 150** has a good adhesion, is water repellent and wear-reducing. As many compressors operate at high temperatures, the oil should have good aging resistance at very low residue formation.

**RAVENOL Kompressorenoel VDL 150** provides a secure lubrication not only in the upper temperature range, also in the cold state of the compressor to achieve a reduction of wear. By selected and coordinated additive composition the tendency to coking and the formation of flammable residues is minimized.

## Application Note

**RAVENOL Kompressorenoel VDL 150** can be used in stationary and mobile compressors with discharge temperatures up to 220°C.

**RAVENOL Kompressorenoel VDL 150** can also be used for circular lubrication of engines and diesel engines where the manufacturer does not stipulate any HD motor oil.

## Characteristics

- Excellent aging resistance
- Best wear protection
- Excellent viscosity-temperature behavior
- Very good cold starting properties
- Low coking tendency

## Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի բնութագրերին	DIN 51352-2, DIN 51506 VDL	
Density at 20 °C	885 kg/m <sup>3</sup>	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	14.4 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	148.2 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	97	DIN ISO 2909
Pourpoint	-20 °C	DIN ISO 3016
Flashpoint	240 °C	DIN EN ISO 2592
Acid Number TAN	0.45 mgKOH/g	ASTM D664

## Out of production

Product	Vendor	Barcode
1 l	1330101-001-01-000	4014835650510
	1330101-001-06-999	2200000032669
5 l	1330101-005-01-000	4014835650558
		2200000038210
20 l	1330101-020-01-000	2200000039033
		4014835650527
60 l	1330101-060-01-999	2200000021212
		2200000033703