

# RAVENOL Kompressorenoel VDL 220

SAE: 220

Mineral



**20 l**

Vendor:  
**1330102-020**



**60 l**

Vendor:  
**1330102-060**  
Vendor:  
1330102-060-01-999



**208 l**

Vendor:  
**1330102-208**  
Vendor:  
1330102-208-01-999

**RAVENOL Kompressorenoel VDL 220** meets the high requirements of DIN 51 506. Specially designed with high quality, age-resistant base oils.

**RAVENOL Kompressorenoel VDL 220** has a good adhesion, is water repellent and wear reducing. As many compressors operate at high temperatures, the oil should have good aging resistance at very low residue formation.

**RAVENOL Kompressorenoel VDL 220** provides a secure lubrication not only in the upper temperature range, also in the cold state of the compressor to achieve a reduction of wear. By selected and coordinated additive composition the tendency to coking and the formation of flammable residues is minimized.

## Application Note

**RAVENOL Kompressorenoel VDL 220** can be used in stationary and mobile compressors with discharge temperatures up to 220°C.

**RAVENOL Kompressorenoel VDL 220** can also be used for lubrication of engines and diesel engines where the manufacturer does not stipulate any HD motor oil.

Exceeds the requirements for VBL- and VCL-oils.

## **Characteristics**

- Excellent aging resistance
- Best wear protection
- Excellent viscosity-temperature behavior
- Very good cold starting properties
- Low coking tendency

## Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
Համապատասխանում է արտադրողի բնութագրերին	DIN 51506 VDL	
Suitable for	ALUP, Atlas Copco Kompessor, CompAir, FIAC, FINI, KAESER, VW	
Density at 20 °C	893 kg/m <sup>3</sup>	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	18.8 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	226.5 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	93	DIN ISO 2909
Pourpoint	-9 °C	DIN ISO 3016
Flashpoint	276 °C	DIN EN ISO 2592

## Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
20 l	1330102-020-01-999	