

# RAVENOL SCR 68 Screw Kompressorenöl

SAE: 68

Mineral



**5 l**

Vendor:  
**1330306-005**



**20 l**

Vendor:  
**1330306-020**



**60 l**

Vendor:  
**1330306-060**



**208 l**

Vendor:  
**1330306-208**

**RAVENOL Screw Kompressorenöl SCR 68** is optimal alloyed, has a high performance level and a wide application area of the whole industry. It is characterised by a good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection. Efficient additives offer an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

## Application Note

**RAVENOL Screw Kompressorenöl SCR 68** is used in compressors.

## Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection

- neutrality of sealing materials

## Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի պահանջներին	FZG Test A 8,3/90, Sperry Vickers I-286-S, Sperry Vickers M-2950-S, Vickers Pumpentest	
Համապատասխանում է արտադրողի բնութագրերին	DIN 51524-2	
Density at 20 °C	866 kg/m <sup>3</sup>	EN ISO 12185
Գույն	light yellow	տեսողական
Մածուցիկություն 100 °C-ում	9 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	68 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	106	DIN ISO 2909
Pourpoint	-27 °C	DIN ISO 3016
Flashpoint	256 °C	DIN EN ISO 2592
Damage loading step	12	DIN 51354/2
Ծերացման կայունություն, TOST	2000 st	DIN 51587

## Out of production

Product	Vendor	Barcode
5 l	1330306-005-01-999	
20 l	1330306-020-01-999	
60 l	1330306-060-01-999	
208 l	1330306-208-01-999	