

# RAVENOL Vakuumpumpenoel ISO VG 32

**SAE: 32W****Mineral****1 l**Vendor:  
**1330704-001****5 l**Vendor:  
**1330704-005****10 l**Vendor:  
**1330704-010****20 l**Vendor:  
**1330704-020**  
Vendor:  
1330704-020-01-999  
Barcode:  
4014835758520**20 l, ecobox**Vendor:  
**1330704-B20****60 l**Vendor:  
**1330704-060**  
Vendor:  
1330704-060-01-999**208 l**Vendor:  
**1330704-208**  
Vendor:  
1330704-208-01-999

**RAVENOL Vakuumpumpenoel ISO VG 32** is optimum alloyed and high level performance industrial oil with a wide range of applications throughout the industry. It is characterized by good viscosity-temperature behavior, high resistance to aging and reliable corrosion protection. Effective additives ensure even under extreme loads an excellent wear protection. Neutral behavior towards sealing materials.

## Application Note

**RAVENOL Vakuumpumpenoel ISO VG 32** is suitable for the lubrication of vacuum pumps (rotary vane pumps, diffusion pumps, turbo pumps), where mineral oils are required, as well as for mist lubrication and crankcase.

**RAVENOL Vakuumpumpenoel ISO VG 32** oil can be used very well for the lubrication of crankcases.

## Characteristics

- High performance level
- Very good viscosity-temperature behavior
- High resistance to aging
- Excellent wear protection
- Reliable corrosion protection
- Neutral to seal materials

## Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի պահանջներին	Alcatel 100, Alcatel 119, Alcatel 120, BUSCH VM, BUSCH VMH, Balzers P3, Becker Vakuumpumpen, Beckmann 19, DIN 51506 VC, Fisherbrand 19, Hyvac 93055, ISO 6743-3 DVA, ISO DVC, Kinney Type A, Leybold-Heraeus 175, PVR Rotant, SAVANT SPO-1, Ulvac 100	
Density at 20 °C	848 kg/m <sup>3</sup>	EN ISO 12185
Գույն	light yellow	տեսողական
Մածուցիկություն 100 °C-ում	5.8 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	32.1 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	123	DIN ISO 2909
Pourpoint	-30 °C	DIN ISO 3016
Flashpoint	224 °C	DIN EN ISO 2592
FZG-Test A/8.3/90 Damage loading step	12 %wt.	DIN 51354/2

## Out of production

Product	Vendor	Barcode
5 l	1330704-005-01-999	
10 l	1330704-010-01-999	
60 l	1330704-060-01-999	
208 l	1330704-208-01-999	