

# RAVENOL Getriebeoel CLP 680

SAE: 680

Mineral



**20 l**

Vendor:  
**1332112-020**  
Vendor:  
1332112-020-01-999



**20 l, ecobox**

Vendor:  
**1332112-B20**



**208 l**

Vendor:  
**1332212-208**  
Vendor:  
1332212-208-01-999



**1 000 l**

Vendor:  
**1332112-700**

**RAVENOL Getriebeoel CLP 680** is a high quality transmission fluid on a mineral oil basis, formulated with unleaded high pressure additives (EP additives). A very good, stable high pressure absorption capacity for impact loads is achieved due to its special combination of ingredients.

**RAVENOL Getriebeoel CLP 680** has a low pour point and therefore, an extremely good low-temperature performance.

## Application Note

**RAVENOL Getriebeoel CLP 680** can be used as a lubricant in almost all industrial gears under heavy load and / or shock load due to its excellent properties.

## Characteristics

- Excellent, stable high pressure absorption capacity for impact loads
- Stable properties in increased temperatures
- A good rust-inhibiting and anticorrosive effect

- Excellent wear protection
- Very good effect against foaming
- A low pour point
- Excellent low-temperature performance

## Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
Համապատասխանում է արտադրողի պահանջներին	AGMA 9005-D94, Clean Panel Coker, S-200 Oxidation Tubes, U.S. Steel 224	
Համապատասխանում է արտադրողի բնութագրերին	DIN 51517-3	
Suitable for	Cincinnati Milacron	
Density at 20 °C	903 kg/m <sup>3</sup>	EN ISO 12185
Գույն	tan	տեսողական
Մածուցիկություն 100 °C-ում	37.4 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	666.2 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	91	DIN ISO 2909
Pourpoint	-12 °C	DIN ISO 3016
Flashpoint	312 °C	DIN EN ISO 2592