

RAVENOL Mehrzweckfett OML



1 կգ

Vendor:
1340101-001
 Vendor:
 1340101-001-03-000
 Barcode:
 4014835200074



5 կգ

Vendor:
1340101-005
 Vendor:
 1340101-005-03-000
 Barcode:
 4014835200159



10 կգ

Vendor:
1340101-010
 Vendor:
 1340101-010-03-000
 Barcode:
 4014835200111



15 կգ

Vendor:
1340101-015



25 կգ

Vendor:
1340101-025
 Vendor:
 1340101-025-03-000
 Barcode:
 4014835200128



100 գրամ

Vendor:
1340101-100
 Vendor:
 1340101-100-04-999
 Barcode:
 4014835844339



180 կգ

Vendor:
1340101-180
 Vendor:
 1340101-180-03-000
 Barcode:
 4014835200142



200 գրամ

Vendor:
1340101-200



400 գրաւ

Vendor:

1340101-400

Vendor:

1340101-400-04-999

Barcode:

4014835768048

RAVENOL Mehrzweckfett OML is lithium saponified multipurpose grease with oxidation and corrosion protective additives.

RAVENOL Mehrzweckfett OML has an extreme mechanical stability and a very low friction value. Therefore it can be transported easily.

Application Note

RAVENOL Mehrzweckfett OML is used for the lubrication of easy loaded antifriction bearings and machine components. It is also suited as multipurpose lubrication grease for vehicles.

Characteristics

- Universal use, multipurpose characteristic for a mixed car pool
- Extreme shear stability
- Excellent corrosion protection
- Excellent wear protection
- Very good mechanical and chemical stability
- Very good aging resistant
- Good pumpability, even at low temperatures

Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի բնութագրերին	DIN 51502 K2K-30, ISO 6743-9: ISO-L-XCCEA2	
Գույն	Light brown	տեսողական
Thickener	lithium soap	DIN 51757
NLGI-Class	2	DIN 51818
Product Classification	K2K-30	DIN 51502
Working Temperature	-30 / +120 °C	DIN 51825
Short term temperature up to	130 °C	DIN 51757
Worked Penetration at 60 Strokes	265-295 mm/10/25°C	ISO 2137
Corrosion (SKF Emcor dist. Water)	1 Korr. Grad	DIN 51802
Dropping Point	180 °C	DIN ISO 2176
Copper Corrosion (24h/120 °C)	1	DIN 51811
Water Resistance (3h/90 °C)	1-90 °C	DIN 51807-1
VKA Pressure Carrying Capacity	2000 - 2200 N	DIN 51350-4
Kinematic Viscosity (Base Oil) at 40 °C	130 mm ² /s	DIN 51562-1

Analogs

Alpine

0101001, 0101005, 0101006, 0101003, 0101002, 0101004

Out of production

Product	Vendor	Barcode
15 կգ	1340101-015-03-000	
400 գրամ	1340101-400-04-000	4014835200081 2200000022035 2200000067678