

RAVENOL LKW FETT BLAU

Mineral



1 կգ

Vendor:
1340117-001
 Vendor:
 1340117-001-03-000
 Barcode:
 4014835661714



5 կգ

Vendor:
1340117-005
 Vendor:
 1340117-005-03-000
 Barcode:
 4014835661752



10 կգ

Vendor:
1340117-010
 Vendor:
 1340117-010-03-000
 Barcode:
 4014835661776



15 կգ

Vendor:
1340117-015



25 կգ

Vendor:
1340117-025
 Vendor:
 1340117-025-03-000
 Barcode:
 4014835661721



180 կգ

Vendor:
1340117-180



400 գրամ

Vendor:
1340117-400
 Vendor:
 1340117-400-04-999
 Barcode:
 4014835768543

RAVENOL LKW FETT BLAU is a lithium saponified multipurpose grease on mineral basis with oxidation and corrosion protective additives.

Because of its special additivation **RAVENOL LKW FETT BLAU** has an excellent pressure absorption capacity, excellent corrosion protection characteristics and a superior mechanical stability.

Application Note

RAVENOL LKW FETT BLAU is used for the lubrication of high loaded friction and antifriction bearings of trucks and construction machines even under the influence of humidity, vibration and shock loading. Functional range from - 30°C up + 125°C (maximum + 140°C). NLGI class 2. Extended lubrication intervals.

Characteristics

- Extreme shear stability
- Excellent corrosion protection
- Very good mechanical and chemical stability
- Very good aging resistance
- Good pump output also at low temperatures

Characteristics

Title	Value	Audit
Հաստատված է արտադրողի կողմից	MAN 283 Li-P2, MB-Approval 267.0	
Համապատասխանում է արտադրողի պահանջներին	DTFR 33B120 (MB 267.0), VW G 052 180	
Համապատասխանում է արտադրողի բնութագրերին	DIN 51502 KP2N-30, ISO 6743-9: ISO-L-XCDIB2, Volvo 97720, Volvo STD	
Գույն	Blue	տեսողական
Thickener	lithium soap	DIN 51757
NLGI-Class	2	DIN 51818
Product Classification	KP2N-30	DIN 51502
Working Temperature	-30 / +140 °C	DIN 51825
Short term temperature up to	220 °C	DIN 51757
Worked Penetration at 60 Strokes	265-295 mm/10/25°C	ISO 2137
Corrosion (SKF Emscor dist. Water)	0 Korr. Grad	DIN 51802
Dropping Point	220 °C	DIN ISO 2176
Copper Corrosion (24h/120 °C)	1	DIN 51811
Water Resistance (3h/90 °C)	1-90 °C	DIN 51807-1
VKA Pressure Carrying Capacity	2200 - 2400 N	DIN 51350-4
Kinematic Viscosity (Base Oil) at 40 °C	220 mm ² /s	DIN 51562-1

Analogs

Alpine

0101046, 0101045, 0101041, 0101042, 0101043, 0101044

Toyota

400776133

Out of production

Product	Vendor	Barcode
15 կգ	1340117-015-03-000	

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
180 կգ	1340117-180-03-000	
400 գրամ	1340117-400-04-000	4014835661745 2200000038098