

RAVENOL Bettbahnöl 32

SAE: 32W

Mineral



208 l

Vendor:

1350374-208

Vendor:

1350374-208-01-999

RAVENOL Bettbahnoel 32 is mineral slide way oil CGLP.

RAVENOL Bettbahnoel 32 is characterized by good lubricating and sliding properties as well as high tackiness.

RAVENOL Bettbahnoel 32 is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

RAVENOL Bettbahnoel 32 is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

Application Note

RAVENOL Bettbahnoel 32 can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary, it can be applied manually. It can also be used for lubricating bearings and gear boxes.

Characteristics

- Wear protection and pressure absorption capacity
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի պահանջներին	Eaton Vickers M-2950-S, Fives Cincinnati P-53, GM LS-2, GM LW-03-1-04	
Համապատասխանում է արտադրողի բնութագրերին	AFNOR E 60-203 HG, AFNOR E 60-203 L-G, DIN 51502 CGLP, DIN 51517-3, DIN 51524-2, GB 11118.1-94 L-HG, GB 11118.1-94 L-HM, ISO 11158 HG, ISO 11158 HM, ISO 19378 GA, ISO 19378 GB, ISO 6743-13 GA, ISO 6743-13 GB, ISO 6743-6 CKC, SAE MS 1007 Type E, SH/T 0361-98 L-G	
Density at 20 °C	854 kg/m ³	EN ISO 12185
Գույն	Yellow	տեսողական
Մածուցիկություն 100 °C-ում	5.75 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	31.9 mm ² /s	DIN 51562-1
Viscosity Index VI	123	DIN ISO 2909
Pourpoint	-33 °C	DIN ISO 3016
Flashpoint	216 °C	DIN EN ISO 2592