

# RAVENOL Bettbahnoel 68

SAE: 68

Mineral



**5 L**

Vendor:  
**1350376-005**



**20 L**

Vendor:  
**1350376-020**  
Vendor:  
1350376-020-01-999  
Barcode:  
4014835763425



**60 L**

Vendor:  
**1350376-060**



**208 L**

Vendor:  
**1350376-208**  
Vendor:  
1350376-208-01-999

**RAVENOL Bettbahnoel 68** is mineral slide way oil CGLP.

**RAVENOL Bettbahnoel 68** is characterized by good lubricating and sliding properties as well as high tackiness.

**RAVENOL Bettbahnoel 68** is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

**RAVENOL Bettbahnoel 68** is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

## Application Note

**RAVENOL Bettbahnoel 68** can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary, it can be applied manually. It can also be used for lubricating bearings and gear boxes.

## Characteristics

- Very good stick-slip characteristics
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

## Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի բնութագրերին	DIN 51502 CGLP, DIN 51517-3, DIN 51524-2	
Density at 20 °C	869 kg/m <sup>3</sup>	EN ISO 12185
Գույն	Yellow	տեսողական
Մածուցիկություն 100 °C-ում	8.8 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	66.6 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	104	DIN ISO 2909
Pourpoint	-27 °C	DIN ISO 3016
Flashpoint	256 °C	DIN EN ISO 2592

## Out of production

Product	Vendor	Barcode
60 l	1350376-060-01-999	