

# RAVENOL TTC Hot Climate -15C Protect C11

**1,5 l**Vendor:  
**1410106-150****5 l**Vendor:  
**1410106-005****10 l**Vendor:  
**1410106-010****20 l**Vendor:  
**1410106-020****60 l**Vendor:  
**1410106-060****208 l**Vendor:  
**1410106-208****1 000 l**Vendor:  
**1410106-700**

**RAVENOL TTC Trad. Techn. Coolant HOT CLIMATE -15°C** is a ready to use, prediluted with water, ethylene-glycol based and time-tested coolant without phosphates, nitrites and amines. This product is

formulated based on a proven inhibitor development as an extended life radiator antifreeze.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

## Application Note

**RAVENOL TTC Trad. Techn. Coolant HOT CLIMATE -15°C** is a prediluted coolant with frost and rust protection for year-round use in automotive engines. Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

**Instructions:** Add **RAVENOL TTC Trad. Techn. Coolant HOT CLIMATE -15°C** to radiator to fill line.

## Characteristics

- Excellent for light metal engines
- Good reserve alkalinity
- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastomers used in automotive radiators

## Characteristics

Title	Value	Audit
ASTM	D1384, D2570, D2809, D3306 Type 1, D4985, D6210 Type 1-FF	
Համապատասխանում է արտադրողի պահանջներին	AFNOR R15-601, BS 6580 (GB), CUNA NC 956-16 (Italien), Chrysler MS-7170, Fiat 9.55523, Fiat PARAFU 11, Ford WSS-M97 B51-A1, IVECO 18-1830, JIS K 2234 (Japan), MAN 324 Type NF, O Norm V 5123, SAE J 1034, UNE 25-361 (Spanien), VW TL 774-C	
Suitable for	Suzuki	
Density at 20 °C	1045 kg/m <sup>3</sup>	EN ISO 12185
Գույն	yellow green	տեսողական
pH - value at 20 °C	7,0-8,4	ASTM D1287
Սառեցման կետ	-15 °C	ASTM D1177

## Out of production

Product	Vendor	Barcode
1,5 l	1410106-150-01-999	
5 l	1410106-005-01-999	
10 l	1410106-010-01-999	
20 l	1410106-020-01-999	
60 l	1410106-060-01-999	
208 l	1410106-208-01-999	