

# RAVENOL MARINEOIL SHPD 25W-40 mineral

Մածուցիկություն: 25W-40

Mineral



**1 Լ**

Հոդված:  
**1163215-001**



**4 Լ**

Հոդված:  
**1163215-004**



**10 Լ**

Հոդված:  
**1163215-010**  
Հոդված:  
1163215-010-01-999



**20 Լ**

Հոդված:  
**1163215-020**  
Հոդված:  
1163215-020-01-999  
Շտրիխ կոդ:  
4014835730427



**20 Լ ecobox**

Հոդված:  
**1163215-B20**



**60 Լ**

Հոդված:  
**1163215-060**



**208 Լ**

Հոդված:  
**1163215-208**



**1 000 Լ**

Հոդված:  
**1163215-700**

**RAVENOL MARINEOIL SHPD SAE 25W-40 mineral** is a modern high additive treated marine engine oil with synthetic additives. It is suitable for inboard marine diesel engines. The high additive content guarantees an excellent effect on the detergent, dispersant and anti corrosion characteristics. It is a top quality product with high safety reserves.

## **Application Note**

**RAVENOL MARINEOIL SHPD SAE 25W-40 mineral** is used in boat engines in case the specification SAE25W-40 is requested.

## **Characteristics**

- suitability for catalysts
- excellent detergent and dispersant characteristics
- very good cold start characteristics
- a high oxidation stability
- an excellent viscosity temperature behaviour
- an excellent corrosion protection
- high safety reserves
- reduction of emissions

## Բնութագրերը

Մտնն	Իմաստը	Սուղիս
API	CF	
Համապատասխանում է արտադրողի պահանջներին	DDC Detroit Diesel, VETUS DEUTZ, Volvo PENTA	
Համապատասխանում է	Caterpillar, IVECO, MAN, MTU, Mercruiser, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, Yanmar	
Հատուկ հզորություն 20°C-ի դեպքում	876 գ/սմ <sup>3</sup>	EN ISO 12185
Գույն	Blue	տեսողական
Մածուցիկություն 100 °C-ում	19 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	161.4 mm <sup>2</sup> /s	DIN 51562-1
Մածուցիկության ինդեքս VI	133	DIN ISO 2909
Ցածր ջերմաստիճանի մածուցիկություն (CCS), -15°C-ում	6100 mPa*s	ASTM D5293
Բյուրեղացման ջերմաստիճան	-30 °C	DIN ISO 3016
Կառուցման ջերմաստիճան	245 °C	DIN EN ISO 2592
TBN	11.1 մգ KOH/գ	ASTM D2896
Շարժիչի տակտայնություն	4T	

## Դադարեցված փաթեթավորում

Փաթեթավորում	Հոդված	Շտրիխ կոդ
1 լ	1163215-001-01-999 1163215-001-06-999	
4 լ	1163215-004-01-999	
10 լ	1163215-010-01-999	
60 լ	1163215-060-01-999	
208 լ	1163215-208-01-999	