

RAVENOL Vakuumpumpenöl ISO VG 150

Մածուցիկություն: 150

Mineral



20 L

Հոդված:
1330708-020
Հոդված:
1330708-020-01-999



20 L ecobox

Հոդված:
1330708-B20



60 L

Հոդված:
1330708-060
Հոդված:
1330708-060-01-999



208 L

Հոդված:
1330708-208
Հոդված:
1330708-208-01-999

RAVENOL Vakuumpumpenöl ISO VG 150 is optimum alloyed and high level performance industrial oil with a wide range of applications throughout the industry. It is characterized by good viscosity-temperature behavior, high resistance to aging and reliable corrosion protection. Effective additives ensure even under extreme loads an excellent wear protection. Neutral behavior towards sealing materials.

Application Note

RAVENOL Vakuumpumpenöl ISO VG 150 is suitable for the lubrication of vacuum pumps (rotary vane pumps, diffusion pumps, turbo pumps), where mineral oils are required, as well as for mist lubrication and crankcase.

RAVENOL Vakuumpumpenöl ISO VG 150 oil pumps can be used very well for the lubrication of crankcases. This vacuum pump oil should not be used in systems with silver or silver alloys.

Characteristics

- High performance level

- Very good viscosity-temperature behavior
- High resistance to aging
- Excellent wear protection
- Reliable corrosion protection
- Very good oxidation stability
- Very good demulsification
- Excellent air release, which largely eliminates foam formation
- Neutral from over plastic seals
- Low pour point

Բնութագրերը

Մնուն	Իմաստը	Մուդիտ
Համապատասխանում է արտադրողի պահանջներին	AFNOR NFE 48-603 HM, AFNOR NFE 48-603 HV, Vickers Vane Pump	
Համապատասխանում է արտադրողի բնութագրերին	DIN 51506 VC, DIN 51524-2	
Հատուկ հզորություն 20°C-ի դեպքում	886 գ/սմ ³	EN ISO 12185
Գույն	Light brown	տեսողական
Մածուցիկություն 100 °C-ում	14.6 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	150 mm ² /s	DIN 51562-1
Մածուցիկության ինդեքս VI	95	DIN ISO 2909
Բյուրեղացման ջերմաստիճան	-21 °C	DIN ISO 3016
Կառուցման ջերմաստիճան	240 °C	DIN EN ISO 2592
Թթվային թիվ, TAN	0.4 մգ KOH/գ	ASTM D664
Սուլֆատային հումքի պարունակություն	0.06 %wt.	DIN 51575