

RAVENOL Super Sägekettenöl

Biodegradable



1 l

Հոդված:

1350301-001

Հոդված:

1350301-001-01-999

Շտրիխ կոդ:

4014835742215



5 l

Հոդված:

1350301-005



20 l

Հոդված:

1350301-020



20 l, ecobox

Հոդված:

1350301-B20



60 l

Հոդված:

1350301-060



208 l

Հոդված:

1350301-208



1 000 l

Հոդված:

1350301-700

RAVENOL Super Saegeketteneol is a rapid biodegradable chainsaw oil, that has successfully passed the KWF Test (Kuratorium für Waldarbeit und Forsttechnik).

RAVENOL Super Saegeketteneol is made from specially selected vegetable oils and toxicological proper additives which do not pollute, because there they are degraded by microorganisms in a short time.

RAVENOL Super Saegeketteneol contains active ingredients based on natural raw materials to improve the mixing behavior of friction and shear-resistant adhesive additives that provide a good lubrication for high-speed chain.

Application Note

RAVENOL Super Saegeketteneol is a chain oil for the lubrication of high-performance saws of all makes. Optimized full lubrication in summer and winter, even under difficult conditions and due to high power reserves when sawing hardwood.

Shelf life of **RAVENOL Super Saegeketteneol**: 18 months at - 20°C to +30°C storage temperature. For cleaning of chain saws, we recommend **RAVENOL Kaltreiniger**.

Characteristics

- Very good viscosity-temperature behavior
- Very good low temperature resistance
- Excellent adhesion and lubrication properties
- High level of protection against wear and corrosion, reduce friction
- Economic consumption, extended service life
- Good long-term low-temperature behavior at -18°C for 100 h: properly filling
- Rapid biodegradability

Բնութագրերը

Մնուն	Իմաստը	Մուդիտ
Հաստատված է արտադրողի կողմից	KWF-Test (verification number 4979)	
Հատուկ հզորություն 20°C-ի դեպքում	920 գ/սմ ³	EN ISO 12185
Գույն	light yellow	տեսողական
Մածուցիկություն 100 °C-ում	22.02 mm ² /s	DIN 51562-1
Մածուցիկություն 40 °C-ում	103.11 mm ² /s	DIN 51562-1
Մածուցիկության ինդեքս VI	243	DIN ISO 2909
Բյուրեղացման ջերմաստիճան	-30 °C	DIN ISO 3016
Կառուցման ջերմաստիճան	324 °C	DIN EN ISO 2592

OEM անալոգներ

Alpine

0101128, 0101129, 0101136, 0101131, 0101130

Husqvarna

577616408

Դադարեցված փաթեթավորում

Փաթեթավորում	Հոդված	Շտրիխ կոդ
1 լ	1350301-001-01-100	2200000037916 4014835150874
5 լ	1350301-005-01-999	
20 լ	1350301-020-01-999	
60 լ	1350301-060-01-999	
208 լ	1350301-208-01-999	